



Kit Developers for Cracks (W500)

This is the first of three products contained in our Kit- Developers for cracks. We suggest a previous cleaning and degreasing of the surface or material interested in testing. The rest can be done with this practical kit!

CRACKS KIT - Kit composed of three spray products that permit the welding or casting of defects such as cracks caused by strain, pitting, porous areas and welding slots. These areas can be identified with ease and precision. For the detection of cracks, fusion defects and open cavities in welded parts. This non-destructive testing method allows efficient checks to be conducted on the quality, conformity and uniformity of surfaces.

How to use: 1) Thoroughly clean and degrease the surface to be treated with the cleaner (blue). 2) Apply the penetrating liquid (red) evenly. 3) Wait 20 minutes for the product to penetrate all defects and dry. 4) Remove excess penetrating liquid using the right solvent and then dry. 5) Spray a thin layer of Crack detector (white) over the area and leave it work. 6) Following reaction with the penetrating liquid in the cracks, the Crack Detector informs the user clearly and unequivocally of any defects in the surface for quick corrections.

Technical specifications:

EAN: 803410889456	
400 ml	
12 Pz.	
Tin-plate can containing under pressure fluid	
White	
Characteristic of solvent	
At 20°C 0,72 ÷ 0,76 g/ml	
Und. 0° C extremely flammable	
4/5 bar	
0,32 mPa.s (20°C) (liquid base)	
465 °C (liquid base)	
2,1 (liquid base)	
240 hPa (20°C) (liquid base)	
> 1000 °C (dry residual TiO2)	



MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com